# PROFISHARK 10G

## IN-DEPTH COPPER AND FIBER NETWORK TROUBLESHOOTING

COMPREHENSIVE 1G/10G COPPER AND FIBER FIFI D TESTING & MONITORING

The ProfiShark 10G is the perfect tool for the field engineer as well as for long-term traffic collection. Easy to use and pocket-sized, this portable device gives you all the flexibility and performance you require for network monitoring.

Combine the ProfiShark 10G with a Windows, Linux or macOS computer through its USB 3.0 port for a complete network analysis solution. The ProfiShark 10G captures packets of all sizes and types and offers a wide assortment of hardware filters, statistics, and capture and configuration options, through the ProfiShark Manager.

# ction. you

### **FEATURES**

- 1G/10G monitoring on USB 3.0
- 4 1G, 10G, copper and fiber SFPs compatible
- USB 3.0 powered
- Hardware aggregation
- SPAN and In-Line modes
- Hardware filtering, deep packet inspection
- Packet slicing
- \$ 8 ns hardware timestamp
- ♦ Customizable real-time statistics
- ♦ In-depth network port diagnostics
- Low level error and bandwidth monitoring
- Direct capture to disk
- o Invisible to the network

### LONG-TERM TRAFFIC CAPTURE

The long-term capture feature is designed to help you catch intermittent problems in the act. By connecting a NAS to the ProfiShark, captures can be done for long periods of time. Included in ProfiShark software package.

- o Ringbuffer or normal capture mode
- Split capture to different files, based on time or size
- Compatible with all Intel-based Synology NAS systems

# TECHNICAL SPECIFICATIONS

CONNECTORS	ACCESSORIES
2 x SFP/SFP+ 1 x USB 3.0 1 x 5 VDC optional input	1.8 m USB 3.0 cable 1.5 m USB A male to DC 5V adapter USB key
DIMENSIONS (WxDxH)	MAX. NETWORK LATENCY
105 x 124 x 26 mm — 4.13 x 4.88 x 1.02 in	10 Gbps: 328 ns
WEIGHT	SYSTEM REQUIREMENTS
280 g — 0.62 lb	Dual Core Processor — 4 GB memory — USB 3.0 port
COMPLIANCE	LEDS
RoHS — CE	4 x Link/Activity — 1 x Power
SUPPORTED OS	
Windows 7 / 8 / 10 (32-bit & 64-bit) — Linux — macOS	

# ORDER REFERENCE

C1AP-10G





