# PROFISHARK 1G+

## ALL-IN-ONE GIGABIT ETHERNET TROUBLESHOOTER

### THE ULTIMATE SOLUTION FOR FIELD TESTING & MONITORING

The ProfiShark 1G+ is the perfect tool for the field engineer as well as for long-term traffic collection. Easy to use and pocket-sized, ProfiShark 1G+ provides flexibility without compromising performance, as it manages to capture 100% of full-duplex 1G traffic passing through.

Combine the ProfiShark 1G+ with a Windows, Linux or macOS computer through its USB 3.0 port for a complete network analysis solution. The ProfiShark 1G+ captures packets of all sizes and types and offers a wide assortment of capture and configuration options, information, and statistics, through the ProfiShark Manager.

ProfiShark 1G+ is fitted with GPS and PPS ports to provide advanced timestamping features.

#### **FEATURES**

- 9 10/100/1G monitoring on USB 3.0
- USB 3.0 powered
- Non-intrusive, fail-safe monitoring
- Hardware aggregation
- SPAN and In-Line modes
- 8 ns hardware timestamp
- GNSS (GPS/GLONASS) UTC timestamping
- PPS synchronization (input/output)
- Real time statistics
- Low level error and bandwidth monitoring
- Direct capture to disk
- Invisible to the network
- PoE compliant
- Full-duplex GbE (2 Gbit/s) capture,
- timestamping, and aggregation at wirespeed
- Compatible with all software packet analyzers

#### ADVANCED TIMESTAMPING

ProfiShark 1G+ provides various timestamping features, such as GPS-linked nanosecond resolution UTC timestamps, SNTP, PPS input/output, and latency compensation options for increased accuracy. These features can be combined in any number of ways to fit your needs.

#### LONG-TERM TRAFFIC CAPTURE

The long-term capture feature is designed to help you catch intermittent problems in the act. By connecting a NAS to the ProfiShark, captures can be done for long periods of time. Included in ProfiShark software package.

- Full-duplex 1G (2 Gbit/s) wirespeed capture
- Ringbuffer or normal capture mode
- Split capture to different files, based on time or size

需要更多信息? 请通过sales@hkaco.com联系我们。

Compatible with all Intel-based Synology NAS systems

## TECHNICAL SPECIFICATIONS

CONNECTORS	ACCESSORIES
2 x RJ45 8 pins 1 x USB 3.0 1 x 5 VDC optional input 1 x SMA female (PPS) 1 x SMA female (GPS)	GPS/GLONASS Antenna 1.8 m USB 3.0 cable RJ45 cable USB key
DIMENSIONS (WxDxH)	MAX. NETWORK LATENCY
105 x 124 x 26 mm — 4.13 x 4.88 x 1.02 in	1 Gbps: 370 ns $-$ 100 Mbps: 660 ns $-$ 10 Mbps: 6600 ns
WEIGHT	SYSTEM REQUIREMENTS
280 g — 0.62 lb	Dual Core Processor — 4 GB memory — USB 3.0 port
COMPLIANCE	LEDS
RoHS	2 x Speed/Status — 2 x Link/Activity — 1 x Sync — 1 x Power
SUPPORTED OS	

**I** 

Windows 7 / 8 / 10 (32-bit & 64-bit) - Linux - macOS

## **ORDER REFERENCE**

## C1AP-1G2

HongKe 



