

GPIB-PC104-XL

PC/104 IEEE-488.2 GPIB Interface

Features

- GPIB interface for PC/104 embedded systems
- ISA (AT/XT) bus interface
- GPIB-32.DLL compatible, runs VEE, LabVIEW etc.
- Windows 2000/XP/Vista, Linux

Overview

The GPIB-PC104 is a PC/104 GPIB controller card that converts any PC/104 based embedded system into a GPIB controller.

It performs all the basic IEEE-488.1 functions such as talker, listener and system controller. The IEEE-488.2 compatible functions make it fully compliant with the IEEE-488.2 specification. In controller applications, you can control typically up to 15 devices (instruments). If operated as a talker/listener (device) interface it does exchange data and state information with the current controller-in-charge of the GPIB bus. The GPIB-PC104 lets Windows and Linux programs control GPIB devices.

Hardware

The GPIB-PC104-XL card plugs onto any PC/104 compatible card stack. An optional flat ribbon cable of 30 cm length connects the card and the 24 pin STD IEEE488 connector.

Software

Windows The Windows software set is included with the GPIB-PC104-XL. It is a WDM driver and supports Windows 2000, XP and Windows Vista on all PC compatible platforms. Libraries and header files are included for the Visual C++, Visual Basic, MINGW and Delphi development systems. An industry standard compatible GPIB-32.DLL supports nearly all applications designed for that interface, including applications developed for LabView 6+, LabWindows, Agilent VEE, TransEra HT-Basic, Agilent Intuilink, and more.



Linux The Linux software set is included with the GPIB-PC104-XL. It supports the Intel (x86) platform Linux kernel versions 2.4 and 2.6. Thus it is compatible with all Linux distributions based on that kernels, e.g. RedHat, SuSE etc. Application development using the GNU Compiler Collection (GCC Version 3) is supported. The ig++ class library provides all interfaces required to control instruments. In addition, IEEE488.2/SCPI compatible instruments can be implemented using Linux based embedded systems.

Specifications

GPIB Capabilities

IEEE 488.1 Capabilities: AH1, SH1, T/TE5, L/LE3, SR1, RL1, PP1/PP2, DC1, DT1, C1, C2, C3, C4, C5

IEEE 488.2 Capabilities: includes the capability to read the following bus lines:EOI, ATN, SRQ, REN, IFC, NRFD, NDAC, DAV

GPIB Handshake Rate: > 1Mbytes/sec

Environmental and Physical

Size: PC/104 form factor, 96 mm H x 90 mm W (3.78 in x 3.55 in)

Weight (net): 65 g

Operating ambient temperature: 0 to 50°C

Storage temperature: -20 to 80°C

Relative humidity: 5 to 95%, noncondensing

Supply Voltage: 5.0 V \pm 5%

Supply Current (max): 250 mA

Ordering Information

GPIB-PC104-XL - Card, Software CDROM

CAB-GPPA - 30 cm flat ribbon cable with IEEE-488 female connector