



XPS-E

Intelligent PROFIBUS DP - RS232 / RS422 / RS485 /
MODBUS ASCII/RTU Gateway

□ Description

This gateway allows you to integrate serial as well as MODBUS-ASCII and -RTU devices quickly, easily and reliably into a PROFIBUS DP network.

All connected serial devices will work as usual, as our gateway depicts all

send and receive sequences 1:1. The data can be accessed swiftly and exactly.

Moreover, our drivers facilitate a pre-processing of data within the gateway. Of course, our drivers can be

customized according to your requirements.


XPS-E is foreseen for top-hat rail mounting.

□ Technical Data

Interfaces	Serial RS232 / 422 / 485 / MODBUS ASCII / RTU PROFIBUS RS485 (isolated)
Baud Rate Serial	Max. 38.400 Bit/s asynchronous (adjustable via PROFIBUS)
Baud Rates PROFIBUS DP	9.6, 19.2, 45.45, 93.75, 187.5, 500 Kbit/s and 1.5, 3, 6, 12 Mbit/s (automatic baud rate detection)
DP-Protocol Version	DP Slave (modular 4 - 240 Bytes)
Power Supply	24 VDC



XPS-E



☐ Order Numbers

Order No.	Item
4000-7-G 0 1 -H-*	XPS-E for top-hat rail with Universal Driver

* Please complete the order number either with E for a documentation in English or D for a documentation in German.

详细资料？请通过sales@hkaco.com联系我们。

上海：021-6728 2707
 北京：010-5781 5040
 广州：400 999 3848
 西安：029-8187 3816



HongKe
 虹科
hkaco.com

广州虹科电子科技有限公司
 测试测量和控制产品 | 定制 | 培训
 华南理工大学国家大学科技园2-504