



### CPU Support

- Onboard Intel® Atom™ x5-E3930 processor Dual Core 1.8GHz

### Main Memory

- On-board type 4GB DDR3L RAM
- Un-buffered and non-ECC

### Display Output

- 1 x HDMI display

### I/O Interface-Front

- 2 x Intel® I210IT GbE LAN ports; support WoL, teaming and PXE
- 4 x USB 3.0 (900mA)
- 1 x External SD card slot (data storage only)
- 1 x Power/1x HDD access LEDs
- 1 x Battery low/1x GP0 programming LED
- 2 x Tx/Rx LEDs
- 1 x ATX power on/off switch

### I/O Interface-Top

- 1 x Remote switch/1 x S3
- 1 x SIM card slot
- 1 x RTC battery socket

### I/O Interface-Bottom

- 2 x DB9, support RS232/422/485 with Auto Flow Control
- 1 x Optional DB9, support 4 x GPI and 4 x GPO

### Storage Device

- Onboard 16GB eMMC
- Optional mSATA module

### Power Requirement

- Power input: typical +24VDC ±20%
- 1 x Optional 24V, 60W power adapter

### Dimensions

- 46.2mm (W) x 100mm (D) x 120mm (H)

### Construction

- Aluminum and Metal Chassis with front access design

### Environment


- Operating temperature: Ambient with air flow: -5°C to 55°C (according to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14)
- Storage temperature: -20°C to 75°C
- Relative humidity: 10% to 93% (non-condensing)
- Shock protection:
  - mSATA/eMMC: 50G, half sine, 11ms, IEC60068-27
- Vibration protection w/ mSATA or eMMC condition:
  - Random: 2Grms @ 5~500 Hz, IEC60068-2-64
  - Sinusoidal: 2Grms @ 5~500 Hz, IEC60068-2-6

### Certifications

- CE approval
  - EN61000-6-2
  - EN61000-6-4
- FCC Class A

### Support OS

- Windows 10 IoT, 32bit/64bit



hkaco.com



关注我们

## Ordering Information

Model	Part Number	Description
eCCF105	+70ECCF105	Intel® Atom™x5-E3930 Dual Core Factory Automation Fanless System with Palm Size form Factor